


ACCESSORY

**S.1483
H 0,5m Ø150mm CYLINDRICAL POLE WITH BASE**

Cylindrical shaped poles consisting of: straight circular section shaft, Ø 150mm, 3mm in thickness, total length 0,50m ,in aluminium EN AW6060.

Suitable for installation to a planted root flange through a base plate 250mm x250mm x12mm in steel S355JO : Suggested reinforced concrete footstall dimension 1m x 1m h 0,7m. Footstall dimension can be calculated according to your country norms and ground properties.

The surface protection treatment is done through hot dip galvanization.

Painting Process: PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content. POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions. Resistance test protection for Marine applications for 1500h.

Note: With the H.500 mm pole, up to 2 Heads can be installed; it is not possible to install the Shift Pro rotosymmetric Triple Head.

**WE RECOMMEND THE USE OF THE FOLLOWING
ACCESSORIES :****S.2009 PLANTED ROOT for CYLINDRICAL POLE****S.2899 POLE BASE COVER**

Accessory available in the following colors: Black (cod.09), Anthracite grey (cod.24)